

RSK 7113768



The Minimax 50 floor drain has a 50 mm side outlet and a low total height of 76mm. It is suitable for installation in concrete joists. The Minimax floor drain comes with a removable NOOD water trap and clamping ring. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain. It is not suitable for installation underneath a bath tub.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

The Minimax 50 floor drain has a 50 mm side outlet and a low total height of 76mm. It is suitable for installation in concrete joists. The Minimax floor drain comes with a removable NOOD water trap and clamping ring. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain. It is not suitable for installation underneath a bath tub.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

RSK Number

7113768

Dimension	Ø50 mm
Floor Construction	Concrete flooring
Floor Covering	Concrete/Resin/Tiles/Vinyl
Function	Side outlet
Item Color	White
Material	PP
Pressure Flow Temp	0,8 l/s
Size	Ø130 mm
Version	No grating