

RSK 7113547



The Oden 75 Side NOOD floor drain has a 75mm side outlet and is for installation in wooden or concrete joists. The Oden floor drain comes complete with a removable NOOD water trap, clamping ring and plastic grate. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. It also acts as a 1m water column and prevents backflow. The floor drain comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

The Oden 75 Side NOOD floor drain has a 75mm side outlet and is for installation in wooden or concrete joists. The Oden floor drain comes complete with a removable NOOD water trap, clamping ring and plastic grate. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. It also acts as a 1m water column and prevents backflow. The floor drain comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

RSK Number

7113547

Dimension	Ø75 mm
Floor Construction	Concrete/Wood
Floor Covering	Concrete/Resin/Tiles/Vinyl
Function	Side outlet
Item Color	White
Material	PP
Pressure Flow Temp	0,8 l/s
Size	Ø150 mm
Version	With NOOD water trap