

# PURUS

## RSK 7118085



The Sigyn 75 floor drain has a 75mm side outlet and is suitable for installation in wooden or concrete joists. The Sigyn floor drain comes with a stainless steel water trap, clamping ring and stainless steel grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

## RSK 7110828

The Sigyn 75 Low floor drain has a 75mm low side outlet. The floor drain has a total height of 120mm and is suitable for installation in wooden or concrete joists. The Sigyn floor drain comes with a stainless steel water trap, clamping ring and stainless steel grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

## Specifications

<b>RSK Number</b>	7118085
<b>Dimension</b>	Ø75 mm
<b>Floor Covering</b>	Concrete/Resin/Tiles/Vinyl
<b>Function</b>	Side outlet
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Pressure Flow Temp</b>	1,0 l/s
<b>Size</b>	Ø150 mm
<b>Surface</b>	Cold rolled (2B)
<b>Version</b>	With stainless steel grating

<b>RSK Number</b>	7110828
<b>Dimension</b>	Ø75 mm
<b>Floor Covering</b>	Concrete/Resin/Tiles/Vinyl
<b>Function</b>	Side outlet
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Pressure Flow Temp</b>	1,0 l/s
<b>Size</b>	Ø150 mm
<b>Surface</b>	Cold rolled (2B)

**Version**

With stainless steel grating

