

RSK 7113598



The Våge 75 Side floor drain has a 75mm side outlet and three Ø32 extra inlets. Only one of the extra inlets should be used. The floor drain has a total height of 163 mm and is suitable for installation in wooden or concrete joists. The Våge floor drain comes complete with a removable water trap with splash guard, extra inlet Ø32, clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain. When installing the Våke floor drain with the Utgård mounting plate, the extension ring should not be used.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

The Våge 75 Side floor drain has a 75mm side outlet and three Ø32 extra inlets. Only one of the extra inlets should be used. The floor drain has a total height of 163 mm and is suitable for installation in wooden or concrete joists. The Våge floor drain comes complete with a removable water trap with splash guard, extra inlet Ø32, clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain. When installing the Våke floor drain with the Utgård mounting plate, the extension ring should not be used.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

RSK Number	7113598
Dimension	Ø75 mm
Floor Construction	Concrete/Wood
Floor Covering	Concrete/Resin/Tiles/Vinyl
Function	Side outlet
Item Color	White
Material	PP
Pressure Flow Temp	1,4 l/s
Size	Ø150 mm
Version	With extra inlet
Other information	Clapming ring 7141315, plastic grating 7138416, extra inlet 32and water trap 7113583 is included as standard. With 3 extra inlet. NOOD-water trap does not fit.