

## RSK 7113580



The Våke 75 Side floor drain has a 75mm side outlet and three extra inlets. Only one of the extra inlets should be used. The floor drain has a total height of 130mm and is suitable for installation in wooden or concrete joists. The Våke floor drain comes complete with a removable water trap, clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain. When installing the Våke floor drain with the Purus Plate (2014 model), the extension ring should not be used.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

### Specifications

|                           |                            |
|---------------------------|----------------------------|
| <b>RSK Number</b>         | 7113580                    |
| <b>Floor Construction</b> | Concrete/Wood              |
| <b>Floor Covering</b>     | Concrete/Resin/Tiles/Vinyl |
| <b>Function</b>           | Side outlet                |
| <b>Item Color</b>         | White                      |
| <b>Material</b>           | PP                         |
| <b>Outlet Dimension</b>   | Ø75 mm                     |

**Pressure Flow  
Temp**

1,0 l/s

**Size**

Ø150 mm

**Version**

With extra inlet

