

## RSK 7113580



The Våke 75 side floor drain has a 75 mm side outlet and three extra Ø32 inlets. Only one of the extra inlets should be used. The floor drain has a total height of 130 mm and is suitable for installation in wooden or concrete joists. The Våke floor drain comes complete with a removable water trap, extra inlet Ø32, clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain. When installing the Våke floor drain with the Utgård mounting plate, the extension ring should not be used.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

## Specifications

<b>RSK Number</b>	7113580
<b>Dimension</b>	Ø75 mm
<b>Floor Construction</b>	Concrete/Wood
<b>Floor Covering</b>	Concrete/Resin/Tiles/Vinyl
<b>Function</b>	Side outlet
<b>Item Color</b>	White
<b>Material</b>	PP

**Pressure Flow  
Temp**

1,0 l/s

**Size**

Ø150 mm

**Version**

With extra inlet

**Other information**

Clapming ring 7141315, plastic grating 7138416, extra inlet 32 and water trap 7113583 is included as standard. With 3 extra inlet. NOOD-water trap does not fit.

