

## Item 53190



PUM Unifit is used in pipe systems for water outlets and provides easy access for inspection and cleaning of the membrane. PUM Unifit is intended for connection to pipe diameter Ø16-32/40 mm using sleeves or transition couplings.

The PUM membrane acts as a mechanical odour barrier, which is closed in its original position and is opened by the water flow, thus replacing a traditional water trap. The membrane's advantages include easy cleaning, compact installation, and good flow capacity. The membrane also functions as secondary ventilation.

## Item 53400

Plastic PUM waste pipe Ø16-32/40mm. The PUM can be used as an odour barrier in the condensation outlets of ventilation and cooling systems. This PUM waste pipe is intended for connection with 18-40 diameter pipes.

## Specifications

PUM Unifit is used in pipe systems for water outlets and provides easy access for inspection and cleaning of the membrane. PUM Unifit is intended for connection to pipe diameter Ø16-32/40 mm using sleeves or transition couplings.

The PUM membrane acts as a mechanical odour barrier, which is closed in its original position and is opened by the water flow, thus replacing a traditional water trap. The membrane's advantages include easy cleaning, compact installation, and good flow capacity. The membrane also functions as secondary

ventilation.

<b>Item Number</b>	53190
<b>Function</b>	Odour trap
<b>Item Color</b>	White
<b>Material</b>	PP, TPE, Silicone
<b>Pressure Flow Temp</b>	0,6 l/s

<b>Item Number</b>	53400
<b>Function</b>	Odour trap
<b>Item Color</b>	White
<b>Material</b>	PP, ABS, TPE, Silicone
<b>Pressure Flow Temp</b>	0,6 l/s