

RSK 7138441



Safe Overflow for vinyl flooring has a 50mm vertical outlet and is adapted for unintentional overflow of water. The Safe Overflow for vinyl comes with a removable automatic odour stop and clamping ring. The automatic odour stop prevents any bad odours from escaping through the drainage system, even if it is dried out. The overflow must not be used as an ordinary floor drain, but can be placed underneath a sink, a kitchen ice maker or similar.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

Safe Overflow for vinyl flooring has a 50mm vertical outlet and is adapted for unintentional overflow of water. The Safe Overflow for vinyl comes with a removable automatic odour stop and clamping ring. The automatic odour stop prevents any bad odours from escaping through the drainage system, even if it is dried out. The overflow must not be used as an ordinary floor drain, but can be placed underneath a sink, a kitchen ice maker or similar.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

RSK Number	7138441
Dimension	Ø50 mm
Floor Construction	Concrete flooring

Floor Covering	Vinyl
Function	Bottom outlet
Item Color	White
Material	PP
Pressure Flow Temp	0,4 l/s
Size	Ø75 mm
Version	With plastic grating