

RSK 7152409



The Balder 75 P untrapped floor drain has a 75 mm vertical outlet and is for installation in wooden or concrete joists. The Balder untrapped floor drain comes with a clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

The Balder 75 P untrapped floor drain has a 75 mm vertical outlet and is for installation in wooden or concrete joists. The Balder untrapped floor drain comes with a clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

RSK Number	7152409
Dimension	Ø75 mm
Floor Construction	Concrete/Wood
Function	Bottom outlet
Item Color	Stainless

Material

PP, Acid-resistant stainless steel 1.4404

**Pressure Flow
Temp**

1,1 l/s

Size

Ø150 mm

Surface

Cold rolled (2B)

Version

With plastic grating