

RSK 7118108



The Sigex 75 P untrapped floor drain has a 75 mm side outlet and three extra inlets. Only one of the extra inlets should be used. The gully is suitable for installation in wooden or concrete joists and comes with a clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

## Specifications

The Sigex 75 P untrapped floor drain has a 75 mm side outlet and three extra inlets. Only one of the extra inlets should be used. The gully is suitable for installation in wooden or concrete joists and comes with a clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

<b>RSK Number</b>	7118108
<b>Dimension</b>	Ø75 mm
<b>Floor Construction</b>	Concrete flooring
<b>Function</b>	Side outlet

<b>Item Color</b>	Stainless
<b>Material</b>	PP, Acid-resistant stainless steel 1.4404
<b>Pressure Flow Temp</b>	1,1 l/s
<b>Size</b>	Ø150 mm
<b>Surface</b>	Cold rolled (2B)
<b>Version</b>	With plastic grating